

Minimum and Maximum sizes (processing)****

Туре	Variant	Maximum (mm)	Minimum (mm)
Annealed	Annealed	3110 x 5000 ¹	
Laminated	Annealed	3210 x 4200 ¹	
Custom Laminated	Annealed/Heat Strengthened/ Toughened	2400 x 4200 ¹	100 x 350
Toughened Toughened (Low E)	4-19mm	2700 x 5000 ¹ 2500 x 5000 ¹	100 x 350 100 x 350
Heat Strengthening	4-10mm	2700 x 5000 ¹	100 x 350
Heat Strengthening (Low E	E) 4-10mm	2500 x 5000 ¹	100 x 350
Insulated Glass Units (IGUs)	4-19mm glass	2800 x 4500	180 x 350
Shaped IGUs	Circle	1500	320
	Rake (minimum per diagram)	diameter	diameter
	Min	nimum 40mm 📥	
Straight-line edging	4-19mm	4500 high	80 x 80
Shape processing	4-19mm	2100 x 4500; & 2360 x 4200	150 x 600; or, 320 diameter
Shape processing (polishing)	5-19mm	1850 x 3540	150 x 600; or, 320 diameter
Heat soaking	4-19mm	2000 x 4500	

1 subject to raw materials availability.

****All of the above are subject to the requirements of AS 2208 and AS 1288.

<u>Please note:</u> Chevron Glass may request adjustments to any order due to manufacturing requirements or W.H.S considerations. Any requirement not covered by these specifications should be referred to our Production Management for approval prior to processing.