

BUREAU VERITAS
Certification



'S' Mark Licence

Awarded to

CHEVRON GLASS PTY LTD

5 BRANDWOOD STREET, ROYAL PARK, SA 5014 AUSTRALIA

Bureau Veritas grants the above organization the right to use the Product Certification 'S' Mark as shown below only in respect of the products described and detailed in the Schedule to this Licence and manufactured in accordance with the requirements of the Standard indicated below under an approved Quality Management System. The Licence is granted subject to the 'Bureau Veritas Conditions of Service' and the 'Rules governing the use of Product Certification Licences'.

STANDARD

AS 2208:2023

Safety glazing materials in buildings

Licence No: 2905

Date Granted: 24 March 2020

Revalidated: 25 February 2025

Expiry Date: 23 March 2030

Signed on behalf of Bureau Veritas

Sam Guindi
Product Certification Manager



This Licence and its associated Schedule remain the property of Bureau Veritas and must be returned if certification is terminated. The constant compliance with the certification requirements is confirmed by regular surveillance measures from Bureau Veritas. In the case of serious non-compliance the certification will be withdrawn and deleted from the Register.

To check the validity of this certificate please contact: **Bureau Veritas Australia Pty Ltd**
Issuing office: Bureau Veritas Pty Ltd, 11/500 Collin Street, Melbourne, Victoria, 3000



SCHEDULE TO PRODUCT CERTIFICATION LICENCE NO: 2905

LICENCE DETAILS

Scheme: 'S' Mark Product Certification

Licensee: CHEVRON GLASS PTY LTD

Address: 5 BRANDWOOD STREET, ROYAL PARK, SA 5014 AUSTRALIA



CONFORMANCE REQUIREMENTS

Standard: AS 2208.2023 Safety glazing materials in buildings

Quality System: Product Certification Quality System Requirements (QSR)

CERTIFIED MODEL OR TYPE

Flat Grade "A" toughened safety glass

Type Glass	Thickness	Colours	Patterns	Interlayer	Maximum Size
Toughened, Patterned, Hard and Sputter Coated	Toughened 4mm to 19mm Pattern 4mm to 6mm	Acid Etch, Clear and Tinted	Cathedral, Narrow Reeded, Satinlite and Spotswood	NA	5000mm (L) x 2700mm (W)
Laminated- Float, Patterned, Hard Coated and Low E	6mm to 39mm	Acid Etched, Clear and Tinted	Cathedral, Narrow Reeded, Satinlite and Spotswood	PVB: .38-3.8mm Clear/Tint EVA: .4-.8mm Clear/Tint XIR: .38mm Tint Sentry: 1.52- 2.28mm Clear	5000mm (L) x 2700mm (W)

Revision Date: 25 February 2025

