

**BUREAU VERITAS**  
Certification



## 'S' Mark Licence

Awarded to

# CHEVRON GLASS PTY LTD

**5 BRANDWOOD STREET, ROYAL PARK, SA 5014 AUSTRALIA**

Bureau Veritas grants the above organization the right to use the Product Certification 'S' Mark as shown below only in respect of the products described and detailed in the Schedule to this Licence and manufactured in accordance with the requirements of the Standard indicated below under an approved Quality Management System. The Licence is granted subject to the 'Bureau Veritas Conditions of Service' and the 'Rules governing the use of Product Certification Licences'.

### STANDARD

## **AS/NZS 2208:1996**

**Safety glazing materials in buildings**

**Licence No: 2905**

**Date Granted: 24 March 2020**

**Expiry Date: 23 March 2025**

Signed on behalf of Bureau Veritas

Sam Guindi  
Product Certification Manager



This Licence and its associated Schedule remain the property of Bureau Veritas and must be returned if certification is terminated. The constant compliance with the certification requirements is confirmed by regular surveillance measures from Bureau Veritas. In the case of serious non-compliance the certification will be withdrawn and deleted from the Register.

To check the validity of this certificate please contact: **Bureau Veritas Australia Pty Ltd**  
Issuing office: Bureau Veritas Pty Ltd, 3/435 Williamstown Road, Port Melbourne, Victoria, 3207



**BUREAU  
VERITAS**



## SCHEDULE TO PRODUCT CERTIFICATION LICENCE NO: 2905

### LICENCE DETAILS

**Scheme:** 'S' Mark Product Certification

**Licensee:** CHEVRON GLASS PTY LTD

**Address:** 5 BRANDWOOD STREET, ROYAL PARK, SA 5014 AUSTRALIA



### CONFORMANCE REQUIREMENTS

**Standard:** AS/NZS 2208:1996 Safety glazing materials in buildings

**Quality System:** Product Certification Quality System Requirements (QSR)

### CERTIFIED MODEL OR TYPE

Flat Grade "A" toughened safety glass

Type Glass	Thickness	Colours	Patterns	Interlayer	Maximum Size
Toughened, Patterned, Hard and Sputter Coated	Toughened 4mm to 12mm Pattern 4mm to 6mm	Acid Etch, Clear and Tinted	Cathedral, Narrow Reeded, Satinlite and Spotswood	NA	4200mm (L) x 2440mm (W)
Laminated-Float, Patterned, Hard Coated and Low E	6mm to 39mm	Acid Etched, Clear and Tinted	Cathedral, Narrow Reeded, Satinlite and Spotswood	<b>PVB:</b> .38-3.8mm Clear/Tint <b>EVA:</b> .4-.8mm Clear/Tint <b>XIR:</b> .38mm Tint <b>Sentry:</b> 1.52-2.28mm Clear	4200mm (L) x 2440mm (W)

Revision Date: 24 March 2020

